



BTS-W STICK MOUNTED WIDE SOLID STRUT THUMBS

A WIDE SOLID STRUT THUMB YOU CAN DEPEND ON

IT'S CURVED, WIDE & MESHES WITH YOUR BUCKET'S TEETH

BTS-W wide solid strut thumbs provide a great grip and is perfect for contractors who prefer a wide solid strut thumb.

The BTS-W is ideal for contractors who need to use a thumb occasionally, or have an application that will require the thumb for long periods of time. It installs easily by simply welding the mounting pad to the excavator's stick. When you're done using the thumb, the BTS-W stores right on the stick with the strut!

There simply isn't a better wide solid strut thumb available. Put a Rockland BTS-W on your excavator for years of dependable service.



SPECIFICATIONS

STANDARD LENGTH

Model	Excavator Wt. (lbs.)	Width/Length (")	Min. Stick Length	TR Range* (")	Tine (qty.)	Weight (lbs.)
ETU30b	25,001 - 33,000 <i>11343 - 14973</i>	16 x 58 <i>406 x 1473</i>	8' 6" <i>2591</i>	44 - 52 <i>1118 - 1321</i>	3	670 <i>304</i>
ETU40b	33,001 - 52,000 <i>14973 - 23593</i>	20 x 65 <i>508 x 1651</i>	9' 1" <i>2769</i>	52 - 60 <i>1320 - 1524</i>	3	1120 <i>512</i>
ETU50b	52,001 - 70,000 <i>23594 - 31760</i>	24 x 78 <i>610 x 1981</i>	9' 9" <i>2972</i>	56 - 64 <i>1422 - 1626</i>	3	1470 <i>667</i>
ETU70b	70,001 - 90,000 <i>31761 - 40835</i>	30 x 83 <i>762 x 2108</i>	11' 2" <i>3404</i>	66 - 74 <i>1676 - 1880</i>	3	1770 <i>803</i>
ETU100b	90,001 - 110,000 <i>40835 - 49909</i>	36 x 101 <i>914 x 2565</i>	13' 3" <i>4039</i>	81 - 89 <i>2057 - 2261</i>	3	2300 <i>1043</i>

Tip Radius (TR) - The bucket tip radius is the distance from your excavator's stick pin to the tip of the tooth on the bucket. If using a coupler, the tip radius is the distance from the center of the stick pin to the tip of the tooth on the bucket. This measurement insures that the thumb is long enough to work with your bucket or bucket(s). A stick mounted thumb should never be allowed to go inside a bucket, nor be too long to work effectively with the bucket.

COUPLER LENGTH

Model	Excavator Wt. (lbs.)	Width/Length (")	Min. Stick Length	TR Range* (")	Tine (qty.)	Weight (lbs.)
ETU40b	33,001 - 52,000 <i>14973 - 23593</i>	20 <i>508</i>	9' 4" <i>2845</i>	62 - 70 <i>1575 - 1778</i>	3	1210 <i>549</i>
ETU50b	52,001 - 70,000 <i>23594 - 31760</i>	24 <i>610</i>	12' 2" <i>7417</i>	74 - 84 <i>1880 - 2134</i>	3	1650 <i>748</i>

***TR Range** - The typical range of TR this thumb will fit. The range exists due to the mounting location of the thumb and machine and bucket model(s) being used. Please call Rockland for a custom thumb quote if your machine's TR range isn't listed.

(mm/kg)

Specifications subject to change without notice.

INSTALLATION INFORMATION

BTS-W stick mounted thumbs are supplied with a mounting plate to be welded to the underside of the excavator stick.

WARRANTY

Rockland BTS-W Thumbs are guaranteed against failure due to defective design, materials or workmanship for a period of two years or 4000 hours.



Distributed by:

ROCKLAND MANUFACTURING CO.
P O BOX 5
800-458-3773

BEDFORD, PA 15522
www.rocklandmfg.com